

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture Neutralizator zapachów ONE SHOT - PACZULI
UFI mixture
Y1M0-P0WM-V00K-WRY4
Other mixture names
Odour Neutraliser ONE SHOT - PATCHOUILI
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Odour neutraliser.
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
Supplier
Name or trade name FRESHTEK JACEK CHOJNACKI
Address ul.Tomasza Edisona 24, Gdańsk, 80-172
Poland
Phone +48 501 621 440
E-mail jacek.freshtek@gmail.com
Competent person responsible for the safety data sheet
Name FRESHTEK JACEK CHOJNACKI
E-mail jacek.freshtek@gmail.com
- 1.4. Emergency telephone number**
+48 501621440 (8:30-16:30)
112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.

Aerosol 1, H222, H229
Eye Irrit. 2, H319
Aquatic Chronic 3, H412
Most serious adverse physico-chemical effects
Pressurised container: May burst if heated. Extremely flammable aerosol.
Most serious adverse effects on human health and the environment
Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements**Hazard pictogram****Signal word**

Danger

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
------	--------------------------------

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear eye protection.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501	Dispose of contents/container to in accordance with local regulations.

Supplemental information

EUH208 Contains 1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one, benzyl salicylate, hexyl 2-hydroxybenzoate, linalool, para-tert-Butylcyclohexyl acetate. May produce an allergic reaction.

2.3. Other hazards

Explosive mixtures can form at ambient temperature due to gas-air mixing. Heating a sealed gas in a sealed vessel can lead to an explosion. It is mildly irritating, slightly narcotic and asphyxiating as oxygen is displaced from the surrounding air. Direct contact with liquefied gas can cause frostbite. The endocrine-disrupting properties of the mixture have not been studied. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 Registration number: 01-2119457610-43	ethyl alcohol	10.86-12.07	Flam. Liq. 2, H225 Eye Irrit. 2, H319	
CAS: 54464-57-2 EC: 259-174-3	1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one	0.6204	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 1, H410	
Index: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0 Registration number: 01-2119457290-43	butanone	<0.3621	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	1
Index: 607-754-00-5 CAS: 118-58-1 EC: 204-262-9 Registration number: 01-2119969442-31	benzyl salicylate	0.2413	Skin Sens. 1B, H317 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	
Index: 607-772-00-3 CAS: 6259-76-3 EC: 228-408-6	hexyl 2-hydroxybenzoate	0.2068	Skin Sens. 1B, H317 Repr. 2, H361d	
Index: 603-235-00-2 CAS: 78-70-6 EC: 201-134-4	linalool	0.1896	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Irrit. 2, H319	
CAS: 32210-23-4 EC: 250-954-9 Registration number: 01-2119976286-24	para-tert-Butylcyclohexyl acetate	0.1034	Skin Sens. 1B, H317	

Notes

1 A substance for which exposure limits are set.

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes.

If swallowed

Unlikely.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

Not expected.

If on skin

Not expected.

If in eyes

When intruding eyes, it can evoke irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

More information

Other relevant information is not available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water jet.

5.2. Special hazards arising from the substance or mixture

Danger of bursting (explosion) when heated. In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Stop leak if possible. Dilute vapors (if accumulated) with water spray. Thoroughly ventilate the spill area. Ventilate the room. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water.

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Do not store with comburent, self-flammable or self-heating substances, organic peroxides, oxidising agents, pyrophoric solids or liquids and explosives.

7.3. Specific end use(s)

Apart from the already mentioned guidelines, it is not necessary to follow any specific recommendations for the use of this product.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value
butanone (CAS: 78-93-3)	OEL 8 hours	600 mg/m ³
	OEL 8 hours	200 ppm
	OEL 15 minutes	900 mg/m ³
	OEL 15 minutes	300 ppm

DNEL

butanone			
Workers / consumers	Route of exposure	Value	Effect
Workers	Inhalation	600 mg/m ³	Chronic effects systemic
Consumers	Inhalation	106 mg/m ³	Chronic effects systemic
Workers	Dermal	1161 mg/kg bw/day	Chronic effects systemic
Consumers	Dermal	412 mg/kg bw/day	Chronic effects systemic
Consumers	Oral	31 mg/kg bw/day	Chronic effects systemic

ethyl alcohol			
Workers / consumers	Route of exposure	Value	Effect
Workers (0)	Dermal	343 mg/kg	Chronic effects systemic
Workers (0)	Inhalation	950 mg/m ³	Chronic effects systemic
Consumers (0)	Oral	87 mg/kg	Chronic effects systemic
Consumers (0)	Dermal	206 mg/kg	Chronic effects systemic
Consumers (0)	Inhalation	114 mg/m ³	Chronic effects systemic

SAFETY DATA SHEET

legal basis:
COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to
Regulation (EC) No 1907/2006 of the European Parliament and of the Council (REACH)

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

linalool			
Workers / consumers	Route of exposure	Value	Effect
Workers (0)	Dermal	5 mg/kg	Acute effects systemic
Workers (0)	Dermal	2.5 mg/kg	Chronic effects systemic
Workers (0)	Inhalation	2.8 mg/m ³	Chronic effects systemic
Workers (0)	Inhalation	16.5 mg/m ³	Acute effects systemic
Consumers (0)	Dermal	2.5 mg/kg	Acute effects systemic
Consumers (0)	Dermal	1.25 mg/kg	Chronic effects systemic
Consumers (0)	Inhalation	0.7 mg/m ³	Chronic effects systemic
Consumers (0)	Inhalation	4.1 mg/m ³	Acute effects systemic
Consumers (0)	Oral	1.2 mg/kg	Acute effects systemic
Consumers (0)	Oral	0.2 mg/kg	Chronic effects systemic

PNEC

butanone	
Route of exposure	Value
Drinking water	55.8 mg/l
Marine water	55.8 mg/l
Water (intermittent release)	55.8 mg/l
Microorganisms in sewage treatment	709 mg/l
Freshwater sediment	284.74 mg/kg
Sea sediments	284.7 mg/kg
Soil (agricultural)	22.5 mg/kg
Food chain	1000 mg/kg of food

ethyl alcohol	
Route of exposure	Value
Microorganisms in sewage treatment	580 mg/l
Soil (agricultural)	0.63 mg/kg
Water (intermittent release)	2.75 mg/l
Oral	0.38 mg/kg
Drinking water	0.96 mg/l
Marine water	0.79 mg/l
Freshwater sediment	3.6 mg/kg
Sea sediments	2.9 mg/kg

linalool	
Route of exposure	Value
Microorganisms in sewage treatment	10 mg/l
Soil (agricultural)	0.327 mg/kg
Water (intermittent release)	2 mg/l
Oral	0.0078 mg/kg
Drinking water	0.2 mg/l
Marine water	0.020 mg/l
Freshwater sediment	2.22 mg/kg
Sea sediments	0.222 mg/kg

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

para-tert-Butylcyclohexyl acetate	
Route of exposure	Value
Microorganisms in sewage treatment	12.2 mg/l
Drinking water	0.0053 mg/l
Marine water	0.00053 mg/l
Soil (agricultural)	0.42 mg/kg
Water (intermittent release)	0.053 mg/l
Freshwater sediment	2.01 mg/kg
Sea sediments	0.21 mg/kg
Food chain	0.067 mg/kg

8.2. Exposure controls

Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed) according to EN 166.

Skin protection

Hand protection: Protective gloves product resistant in accordance with EN ISO 374-1. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Flammable product, avoid contact with hot surfaces, sources of fire and high temperatures.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	data not available
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	not determined
Flammability	extremely flammable aerosol
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	not determined
pH	7-8 (undiluted)
Kinematic viscosity	not applicable
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	not determined
Vapour pressure	data not available
Density and/or relative density	not determined
Relative vapour density	not determined
Particle characteristics	not applicable
Form	aerosol dispenser: spray aerosol

9.2. Other information

none

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

SECTION 10: Stability and reactivity

10.1. Reactivity

When used in the standard way, there is not any dangerous reaction with other substances.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Contact with sources of ignition makes product set on fire.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents. Do not store with comburents, self-flammable or self-heating substances, organic peroxides, oxidising agents, pyrophoric solids or liquids and explosives.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture. No toxicological effects are expected if occupational exposure limits are not exceeded. It does not meet the criteria for classification as a CMR category 1A or 1B substance, according to point 1.3.1 of Annex I to Regulation (EC) No 1272/2008 (CLP).

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met.

butanone						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀		3460 mg/kg		Rat	
Dermal	LD ₅₀	OECD 402	>5000 mg/kg		Rabbit	
Inhalation (vapor)	LC ₅₀		>7500 ppm	4 hours	Rat	

ethyl alcohol						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀		6200 mg/kg		Rat	
Dermal	LD ₅₀		20000 mg/kg		Rabbit	
Inhalation	LC ₅₀		124.7 mg/l	48 hours	Rat	

linalool						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀		3000 mg/kg		Rat	
Dermal	LD ₅₀		5610 mg/kg		Rabbit	

para-tert-Butylcyclohexyl acetate						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀		3370 mg/kg		Rat (Rattus norvegicus)	

SAFETY DATA SHEET

legal basis:
COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to
Regulation (EC) No 1907/2006 of the European Parliament and of the Council (REACH)

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

Skin corrosion/irritation

Based on the available data, the criteria for classification of the mixture are not met.

butanone			
Route of exposure	Result	Exposure time	Species
	Drying and cracking of the skin		

Irritation

ethyl alcohol					
Route of exposure	Result	Method	Exposure time	Species	Source
Eye	Irritating	OECD 405	21 days	Rabbit	podrażnienie odwracalne

Serious eye damage/irritation

Causes serious eye irritation.

butanone				
Route of exposure	Result	Method	Exposure time	Species
Eye	Slightly irritating	OECD 405	21 days	Rabbit

Respiratory or skin sensitisation

Based on the available data, the criteria for classification of the mixture are not met.

Germ cell mutagenicity

Based on the available data, the criteria for classification of the mixture are not met.

ethyl alcohol						
Result	Method	Exposure time	Specific target organ	Species	Sex	Source
Indeterminate	in vivo			Mouse		Rodzaj badania: Badanie dominującego genu letalnego (gameta) posób podania dawki: Połknięcie

Carcinogenicity

Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

Based on the available data, the criteria for classification of the mixture are not met.

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

Toxicity for specific target organ - single exposure

Based on the available data, the criteria for classification of the mixture are not met.

butanone					
Route of exposure	Parameter	Value	Result	Species	Sex
			Drowsiness, Dizziness		

Toxicity for specific target organ - repeated exposure

Based on the available data, the criteria for classification of the mixture are not met.

Repeated dose toxicity

butanone							
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Inhalation (dust/mist)	NOAEL		OECD 413	5014 ppm	90 days	Rat	

ethyl alcohol							
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL			1280 mg/kg	90 days	Rat	
Oral	LOAEL			3156 mg/kg	90 days	Rat	

Aspiration hazard

Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information

12.1. Toxicity

It is not expected to be harmful to the aquatic environment.

Acute toxicity

1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one					
Parameter	Method	Value	Exposure time	Species	Environment
LC ₅₀		1-10 mg/l	96 hours	Fish	
EC ₅₀		1-10 mg/l	48 hours	Crustaceans	
EC ₅₀		1-10 mg/l	72 hours	Algae	

butanone					
Parameter	Method	Value	Exposure time	Species	Environment
LC ₅₀	OECD 203	2993 mg/l	96 hours	Fish (Pimephales promelas)	
EC ₅₀	OECD 202	308 mg/l	48 hours	Daphnia (Daphnia magna)	
EC ₅₀	OECD 201	2029 mg/l	96 hours	Algae (Selenastrum capricornutum)	

SAFETY DATA SHEET

legal basis:
COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to
Regulation (EC) No 1907/2006 of the European Parliament and of the Council (REACH)

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

ethyl alcohol					
Parameter	Method	Value	Exposure time	Species	Environment
LC ₅₀		11000 mg/l	96 hours	Fish (Alburnus alburnus)	
EC ₅₀		9268 mg/l	48 hours	Daphnia (Daphnia magna)	
EC ₅₀		1450 mg/l	192 hours	Algae and other aquatic plants (Microcystis aeruginosa)	
ErC ₅₀		275 mg/l	72 hours	Algae and other aquatic plants (Chlorella vulgaris)	
EC ₁₀		11.5 mg/l	72 hours	Algae and other aquatic plants (Chlorella vulgaris)	
EC ₅₀		6500 mg/l	16 hours	Microorganisms (Pseudomonas putida)	

Chronic toxicity

ethyl alcohol				
Parameter	Value	Exposure time	Species	Environment
NOEC	250 mg/l		Fish (Danio rerio)	
NOEC	2 mg/l		Crustaceans (Ceriodaphnia dubia)	
NOEC	9.6 mg/l	9 days	Aquatic invertebrates (Daphnia magna)	

12.2. Persistence and degradability

There are no ecotoxicological data available for the product.

Biodegradability

butanone					
Parameter	Method	Value	Exposure time	Environment	Result
	OECD 301D	98 %	28 days		Easily biodegradable

ethyl alcohol					
Parameter	Method	Value	Exposure time	Environment	Result
		89 %	14 days		Easily biodegradable
		89 %	14 days		

linalool					
Parameter	Method	Value	Exposure time	Environment	Result
		90 %	28 days		

12.3. Bioaccumulative potential

There are no ecotoxicological data available for the product.

butanone	
Parameter	Value
Log Pow	0.3

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

ethyl alcohol	
Parameter	Value
BCF	3
Log Pow	-0.31

linalool	
Parameter	Value
BCF	39
Log Pow	2.97

12.4. Mobility in soil

There are no ecotoxicological data available for the product.

ethyl alcohol	
Parameter	Value
Koc	1

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Unknown.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

A container that is free of residual product can be treated as a waste that does not pose a hazard. Do not puncture, cut or weld empty packaging. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not dispose unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

16 05 04* gases in pressure containers (including halons) containing hazardous substances

Packaging waste type code

15 01 11* metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

14.4. Packing group

not relevant

14.5. Environmental hazards

Product is not an environmental hazard according to the criteria of the UN Model Regulations.

14.6. Special precautions for user


Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable - not intended for bulk transportation.

Additional information

Hazard identification No.



UN number

5F

Classification code

2.1

Safety signs




Road transport - ADR

Limited quantities

1 L

Sign



Tunnel restriction code

(D)

Air transport - ICAO/IATA

Packaging instructions passenger

203

Cargo packaging instructions

203

Marine transport - IMDG

EmS (emergency plan)

F-D, S-U

MFAG

620

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

National regulations (Germany)

WGK Water hazard class:

WGK 1 - slightly hazardous to water

15.2. Chemical safety assessment

For mixtures, a chemical safety assessment is not required.

More information

Seveso Directive 2012/18/EU (Seveso III): P3a FLAMMABLE AEROSOLS

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH066

Repeated exposure may cause skin dryness or cracking.

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

EUH208	Contains 1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one, benzyl salicylate, hexyl 2-hydroxybenzoate, linalool, para-tert-Butylcyclohexyl acetate. May produce an allergic reaction.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear eye protection.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501	Dispose of contents/container to in accordance with local regulations.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	Agreement concerning the international carriage of dangerous goods by road
Aerosol	Aerosol
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₁₀	Concentration of a substance when it is affected 10 % of the population
EC ₅₀	Concentration of a substance when it is affected 50 % of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEL	Lowest observed adverse effect level
log Kow	Octanol-water partition coefficient
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration

Neutralizator zapachów ONE SHOT - PACZULI

Creation date	17th June 2025	Version	1
Revision date			

OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
Press. Gas (Comp.)	Gas under pressure: compressed gas
Press. Gas (Diss.)	Gas under pressure: dissolved gas
Press. Gas (Liq.)	Gas under pressure: liquefied gas
Press. Gas (Ref. Liq.)	Gas under pressure: refrigerated liquefied gas
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Repr.	Reproductive toxicity
RID	Agreement on the transport of dangerous goods by rail
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity - single exposure
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

Uses advised against: Any type of use not listed in this Safety Data Sheet.

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available.

The changes (which information has been added, deleted or modified)

Version 1.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.